



## **Roofglaze Rooflights Ltd**

Tel: 01480 474797

To be read with Preliminaries/ General Conditions.

### **PRELIMINARY INFORMATION/ REQUIREMENTS**

Site dimensions must be taken and agreed prior to the commencement of fabrication of the Rooflight Frames. All information should be read in conjunction with the approved drawings, specs and quotation.

### **COMPONENTS**

#### ALUMINIUM ROOFLIGHTS:

- A self-supported system, for applications in commercial or residential buildings.
- The system is installed to a builder's kerb, finished by roofing membrane. Recommended minimum pitch is 5° to help shed water but can be installed almost flat. The maximum recommended pitch is 70°. Max pitch without a head flashing 25°.
- Double or triple glazed hermetically sealed glass, UV resistant silicone seal. Optional painted or sandblasted perimeter border available upon request. Painted border not available on annealed glass.
- Frames are manufactured from extruded aluminium section to EN 12020-1:2001.
- Polyamide Thermal Break to the glazing frame makes it fully thermally broken and thermally efficient.
- Weather tested to CWCT A4 Air Permeability & R7 Watertightness at Peak Pressure 600 pa.
- Tested for non-fragility to CWCT TN66/67 & TN92 Class 1 or Class 2.
- Polyester Powder Coated aluminium to BS EN 12206-1:2004.
- BS 476 - External Fire – AA, Non-Combustibility – Class O, Surface Spread Class 1.
- **15 Year warranty.**

#### PRODUCT

- Type: **Fixed Flatglass Single Pane**
- A technical drawing of this product is available from:  
<https://www.roofglaze.co.uk/resources/product-drawings/>

Frame: Extruded aluminium section to BS1474, EN 12020-1:2001.

Kerb: Recommended 150mm high, minimum 75mm wide excluding finishes, top to be in one continuous plane.

- Manufacturer:

ROOFGLAZE ROOFLIGHTS LTD  
11 Howard Road, Eaton Socon  
St Neots, Cambridgeshire  
PE19 8ET  
Tel: 01480 474797  
Web: [www.roofglaze.co.uk](http://www.roofglaze.co.uk)  
E-mail: [info@roofglaze.co.uk](mailto:info@roofglaze.co.uk)

Dirt Resistant Coatings - Pilkington Activ Self Cleaning – requires 15° kerb pitch or greater  
All pitches - Ritec ClearShield easy clean coating

Solar Control Options - SGG COOL-LITE SKN solar control range or similar approved  
Body Tint Anti-sun - Pilkington Optifloat Tint range or similar approved

- Typical Thermal Performance:



Double glazed total product U-value = 1.5 W/m<sup>2</sup>.K typical but as low as 0.7 W/m<sup>2</sup>.K to special order

Triple glazed total product U-value = 1.1 W/m<sup>2</sup>.K but as low as 0.5 W/m<sup>2</sup>.K to special order

Area weighted U-values based upon a typical 1m x 2m unit

- Service:

Roofglaze Rooflights can provide a design and specification service and it is recommended that they are consulted early in the design process.

Roofglaze Rooflights would always recommend that a Flatglass unit should be installed to a minimum pitch of 5°, up to 2.0m span (down slope) and at a min. 10° over 2.0m span. This is to help facilitate water run-off thus reducing water ponding and to help alleviate the build-up of silt deposits. This is also required so that the unit drains properly.

### Fixed Single Pane Flatglass

#### Type 1

- Manufacturer: Roofglaze Rooflights Ltd
  - Web: [www.roofglaze.co.uk](http://www.roofglaze.co.uk)
  - Tel: +44 (0)1480 474797
  - Product reference: Fixed Single Pane Flatglass
- Type: *Rectangular Square Circular Bespoke*
- Size: *As per drawing:*
- Frame finish: *Standard Marine Grade Polyester Powder Coated RAL: Colour T.B.C.*
- Glazing:
  - Outer pane: *4mm 6mm 8mm 10mm 12mm* heat soak tested toughened glass
  - Cavity: *24mm 20mm 16mm 14mm* 90% argon filled, silicone bonded + warm edge spacer
  - Inner pane: *4mm 6mm 8mm* heat soak tested toughened *6.8mm 8.8mm 10.8mm 13.5mm*  
*annealed laminated heat strengthened laminated*
  - Soft coat Low-E coating: *Always required to meet or exceed AD Part L target u-values*
- Additional requirements/  
options: Detailed site survey required prior to manufacture.  
Min. 150mm high x 75mm thick structurally sound kerb not by Roofglaze Rooflights.  
Flashing of kerb, not by Roofglaze Rooflights.  
Rooflight to comprise one pane of glass.  
*PVB Laminate/ SGP Laminate.*  
*Coloured laminated glass.*  
*Heat strengthened laminate.*  
*High performance solar control options.*  
*Obscure glazing available, sandblast all over, coloured PVB interlayer or satin glass.*  
*Body tint glass grey, blue, bronze or green.*  
*Ritec ClearShield easy clean coating.*  
*Active self-cleaning glass. Minimum pitch greater than 15° + chemical resistant silicone.*  
*Wall abutment to head verge head & verge head & both verges.*  
*One raked edge Multiple raked edges.*  
Triple glazed.  
Integrated top hung opening vents available with 24v or 230v chain link actuators.  
Integrated access hatch 800mm x 800mm maximum. Minimum pitch 15°.  
Acoustic laminated glass.



- Improved U-values with Super Low-E coating.
- Dot matrix pattern.
- Extension to frame to accommodate larger specialist glass specs.
- Low iron glass.
- Insulated aluminium panel.
- Modular timber kerb at 5° pitch or similar.
- Integrated blind within the IGU – white (please specify opening direction)

### More about Fixed Flatglass:

- A self-supported rooflight for applications in commercial and residential buildings.
- Building Regulations (E&W) Approved Document L compliant design to achieve low U-value targets.
- Silicone jointed glazing for a flush outer surface.
- Ventilation option for natural ventilation in accordance with Building Regulation (E&W) Approved Document F available.
- Automatic Opening Vents (AOV) for natural ventilation can also be accommodated.
- Designed to be installed to a weathered builder's kerb, minimum 5° pitch.
- AA fire rated: AA designation (National Class) designation or Broof(t4) (European class)
- Non-fragile to ACR[M]:001 Class B and with laminated glass CWCT TN92 class 2.
- Double or triple glazed units can be contained within a single frame to cater for a wide range of sizes.
- Elliptical, circular and irregular shaped rooflights are also available.
- Designed to standard loadings of 640 N/m<sup>2</sup> (snow) and 750 N/m<sup>2</sup> (wind) and in accordance with the following British Standards:
  - BS 6375-1: Weather tightness.
  - BS EN 1026: Air permeability.
  - BS EN 1027: Water tightness test.
  - BS EN 12211: Wind resistance test.
  - BS EN 12206-1:2004: Polyester Powder Coating.
- Third party Air Permeability and Weather testing carried out at the BRE, report available upon request.
- Fully thermally broken glazing frame giving superior protection against heat loss and condensation.
- Aluminium frame weight = 3.22 kg/m.
- **15 Year warranty.**