

Hinged Flatglass Rooflights

A contemporary, easy-to-use ventilation and daylighting solution for modern buildings



Key Features & Benefits

- 15 year warranty*
- Fully thermally-broken aluminium glazing frame prevents cold bridging, reducing the risk of condensation
- Electric (230v as standard, with 24v options) and Manual Hinged (Wormgear Spindle) rooflights are available
- Excellent thermal performance, with total system U-values as low as 0.6 W/m²K achievable
- Quick and easy to install on-site
- Designed to be installed on pitches from 3 degrees
- Recommended minimum pitch of 5 degrees to help shed water
- Minimal framework: daylight is maximised while the visible framework is minimised

Frame Specification

- The Hinged Flatglass rooflight frame is manufactured from extruded aluminium section to BS 1474, EN 12020-1:2001
- Polyamide thermal break within the glazing frame makes it fully thermally-broken and extremely thermally-efficient
- Polyester Powder Coated Aluminium to BS EN 12206-1:2004
- **RAL Colours:** Anthracite Grey (RAL 7016) frames on stock rooflights
- White (RAL 9010) and Black (RAL 9005) frames are also available as standard options
- Bespoke RAL colour options available on request

Critical Kerb External Dimensions (Standard Glass Specification)

- Min. Kerb Height:** 150mm (at the eaves end)
- Min. Kerb Thickness:** 75mm (excluding finishes)
- Max. Size (Square):** 1850mm x 1850mm
- Max. Size (Rectangular):** Dependent on glass specification
- Min. Size:** 600mm x 600mm
- Min. Pitch:** 3°
- Chain Stroke (Electric Hinged):** 200mm as standard (100mm and 300mm options available)
- Worm Screw Stroke (Manual Hinged):** 300mm Max.

British Standards Compliance

- BS 6375-1: Weathertightness
- BS EN 1026: Air Permeability
- BS EN 1027: Watertightness
- BS EN 12211: Wind Resistance
- BS EN 12206-1:2004: Polyester Powder Coating

Design Loadings

- Snow:** 640 N/m²
- Wind:** 750 N/m²
- Product Weight:** From 51 kg/m²



Product Testing & Certification

- **Weathertightness:** CWCT Class A4 Air leakage, Resistance to Wind Class E2400 Pa and Watertightness Class R7
- **Non-fragility:** CWCT TN66/67 and TN92, with Class 1 and Class 2 compliant solutions available
- **AA Fire-rated:** AA Designation (National Class) or BROF (T4) European Class and Euro Class A1 non-combustible

Rooflight Control Options

- Supplied with a white Rocker Switch as standard (Electric Hinged)
- MB08 Temperature, Wind and Rain Sensors (plus remote options)
- Touchpoint and Key Switches, plus Multi-zone operation options
- Telescopic winding pole up to 3.0m (Manual Hinged)

Glass Specification

Double Glazed - Standard:

- Outer:** 4mm or 6mm Clear Heat Soak Tested Toughened glass
- Cavity:** 24mm or 20mm Argon filled with Swisspacer warm edge spacer silicone bonded
- Inner:** 4mm or 6mm Clear Heat Soak Tested Toughened glass with Soft Low-E coating to cavity face

Double Glazed (CWCT Class 2 Non-fragile):

- Outer:** 6mm Clear Heat Soak Tested Toughened glass with Soft Low-E coating to cavity face
- Cavity:** 16mm Argon filled with Swisspacer warm edge spacer silicone bonded
- Inner:** 9.5mm Laminated glass with PVB interlayer and polished edges

Rooflight Performance

- Building Regulations (E&W)
- Approved Document L compliant design to achieve low U-values
- U-values:** As low as 0.6 W/m²K
- G-values:** As low as 0.19
- Light Transmission:** Up to 78.5%

Bespoke Glass Options

- Solar Control
- Privacy Glass
- Body Tinted
- Acoustic Laminate
- Coloured Glass
- Easy-clean Coatings (Ritec)

- CUIIN Advanced Thermal Performance
- Triple Glazed and 8.8mm Laminated Inner options are available on request



Get in touch for Technical and Estimating Advice:

T: 01480 474 797 | W: www.roofglaze.co.uk
E: rgrestimating@roofglaze.co.uk

Roofglaze Ltd

11 Howard Road, Eaton Socon, St Neots, Cambridgeshire PE19 8ET